

What is claimed is:

Sub
A2

10027390-122101
TOTAL "06/2007"

1. An apparatus for communication to a network and for use with at least a first and second object, each of which objects is characterized by a location, comprising:

a location circuit installed in each object which detects location information of the corresponding object in real-time;

a processor with memory installed in each object coupled to the location circuit, which processor receives the location information and activates responsive functions according to the corresponding object's current location and which processor stores events of the corresponding object in a history file; and

a communication circuit installed in each object coupled to the processor in the same object to transmit messages to the network and to receive messages from the network,

where the processor corresponding to the first object automatically activates selected functions controlling the first object in response to the location of the second object.

2. The apparatus of claim 1 in further combination with at least one satellite of a global positioning system and where the location circuit comprises a GPS receiver communicating with the at least one satellite of the global positioning system.

1 3. The apparatus of claim 1 where the location circuit communicates
2 through the communication circuit with a terrestrial location detection network.

1 4. The apparatus of claim 1 in further combination with at least one
2 satellite of a global positioning system and where the location circuit comprises a
3 GPS receiver communicating with the at least one satellite of the global
4 positioning system and a terrestrial location detection network in combination.

1 5. The apparatus of claim 4 where the processor in each object
2 controls the location circuit in the same object to first determine location of the
3 corresponding object using the GPS receiver and then uses the terrestrial
4 location detection network to determine location only if the GPS receiver fails to
5 provide valid locational information.

1 6. The apparatus of claim 1 where the events of the history file stored
2 by the processor in each object includes location, time of day, speed, and
3 direction of the corresponding object for each event.

1 7. The apparatus of claim 6 where the events of the history file stored
2 by the processor in each object include the type of the event.

1002390-1001
TOTTENHAM 06/2/2001

1 8. The apparatus of claim 7 where the events of the history file stored
2 by the processor in each object include sent and received messages.

1 9. The apparatus of claim 1 in further combination with a remote
2 server communicated through the network with one of the first and second
3 objects where an event of the history file stored by the processor in each object
4 is sent to the remote server and then cleared by the processor in the
5 corresponding object from the memory in the corresponding object.

1 10. The apparatus of claim 9 is cleared by the processor in each object
2 from memory in the corresponding object on a periodic basis.

1 11. The apparatus of claim 9 is cleared by the processor in each object
2 from memory in the corresponding object at the time that event of the history file
3 stored by the processor in each object is sent to the remote server.

1 12. The apparatus of claim 1 where the first or second object can each
2 be independently moving or stationary.

1 13. The apparatus of claim 1 where the communication circuit in each
2 object comprises a plurality of wireless modems, a satellite modem and a
3 frequency adjustable transceiver in each object coupled to the wireless modems

10027390-122401

4 and satellite modem in the corresponding object, wherein the processor in each
 5 object is coupled to and controls the frequency adjustable transceiver in the
 6 corresponding object to select a best signal from the wireless modems in the
 7 corresponding object, but if the best signal from the wireless modems in the
 8 corresponding object fails to satisfy a predetermined threshold, then the
 9 processor in each object controls the frequency adjustable transceiver in the
 10 corresponding object to select a signal from the satellite modem in the
 11 corresponding object.

1 14. The apparatus of claim 1 where the processor in each object stores
 2 all valid location fixes and where the location circuit in the corresponding object
 3 comprises in the corresponding object a GPS engine board, a receiver for
 4 communication to the network coupled to the GPS engine board, and a position
 5 computation circuit coupled to the receiver, the GPS engine board, receiver and
 6 position computation circuit being coupled to the processor, where the processor
 7 in each object controls the GPS engine board in the corresponding object to
 8 determine location of the corresponding object, but if the GPS engine board in
 9 the corresponding object fails to provide a valid location fix, the processor in the
 10 corresponding object then controls the position computation circuit in the
 11 corresponding object to provide a location by dead reckoning based on the last
 12 recorded valid location fix.

1 15. The apparatus of claim 14 where the position computation circuit in
2 the each object comprises a gyro and a speed sensor to provide dead reckoning
3 input data from which the processor in the corresponding object calculates a
4 dead reckoning location.

1 16. The apparatus of claim 15 where the gyro in each object comprises
2 a three dimensional gyro.

1 17. The apparatus of claim 1 further comprising a plurality of
2 input/output ports in the corresponding object coupled to the processor in each
3 object and a plurality of external devices in the corresponding object coupled the
4 plurality of input/output ports in the object.

1 18. A method comprising:
2 detecting location information of a plurality of objects in real-time in a
3 corresponding location circuit in each object;
4 inputting the location information into a processor in each object with
5 memory in the corresponding object coupled to the location circuit in the
6 corresponding object;
7 storing events of each object in a history file in the memory in the
8 corresponding object; and
9 transmitting messages from each of the objects to a network; and

10027390-122101

10 activating a responsive function in at least one of the objects through the
11 network according to the corresponding object's location, where the processor
12 corresponding to the at least one object automatically activates a selected
13 function to control the same object in response to the location of the other one of
14 the objects.

1 19. The method of claim 18 in further combination with at least one
2 satellite of a global positioning system and where detecting location information
3 of at least one object in real-time comprises communicating a GPS receiver in
4 the corresponding object with at least one satellite of the global positioning
5 system.

1 20. The method of claim 18 where detecting location information of at
2 least one object in real-time comprises communicating the corresponding object
3 with a terrestrial location detection network.

4 21. The method of claim 18 in further combination with at least one
5 satellite of a global positioning system and where detecting location information
6 of at least one object in real-time comprises communicating a GPS receiver in
7 the corresponding object with at least one satellite of the global positioning
8 system and a terrestrial location detection network in combination.

10027390-123101

1 22. The method of claim 21 where communicating a GPS receiver in
2 the corresponding object with at least one satellite of the global positioning
3 system and a terrestrial location detection network in combination comprises
4 controlling the location circuit in the corresponding object to first determine
5 location using the GPS receiver in the corresponding object and then
6 communicating the corresponding object with the terrestrial location detection
7 network to determine location only if the GPS receiver in the corresponding
8 object fails to provide valid locational information.

1 23. The method of claim 18 where storing events of the corresponding
2 object in a history file comprises storing location, time of day, speed, and
3 direction of the corresponding object for each event relating to the corresponding
4 object.

1 24. The method of claim 23 where storing events of the corresponding
2 object in a history file comprises storing the type of the event relating to the
3 corresponding object.

1 25. The method of claim 24 where storing events of the corresponding
2 object in a history file comprises storing sent and received messages relating to
3 the corresponding object in the corresponding object.

10027390-122101

1 26. The method of claim 18 further comprising communicating with a
2 remote server through the network with one objects where an event of the history
3 file stored by the processor in the corresponding object is sent to the remote
4 server and then cleared by the processor in the corresponding object from
5 memory in the corresponding object.

1 27. The method of claim 26 where clearing the event of the history file
2 in the corresponding object is performed on a periodic basis.

3 28. The method of claim 26 where clearing the event of the history file
4 in the corresponding object is performed at the time that event of the history file
5 stored by the processor in the corresponding object is sent to the remote server.

1 29. The method of claim 18 where at least one of the objects is moving.

1 30. The method of claim 18 where at least one of the objects is
2 stationary.

1 31. The method of claim 18 where transmitting messages from each of
2 the objects to a network comprises in each of the corresponding objects
3 transmitting through a plurality of wireless modems, a satellite modem and a
4 frequency adjustable transceiver in each of the corresponding objects coupled to

the wireless modems and satellite modem in the corresponding objects, wherein the processor in each of the corresponding objects is coupled to and controls the frequency adjustable transceiver in the corresponding object to select a best signal from the wireless modems in the corresponding object, but if the best signal from the wireless modems in the corresponding object fails to satisfy a predetermined threshold, then the processor in the corresponding object controls the frequency adjustable transceiver in the corresponding object to select a signal from the satellite modem in the corresponding object.

32. The method of claim 18 further comprising storing all valid location fixes in the corresponding object and where detecting location information in the corresponding object comprises operating in each object a GPS engine board, a receiver for communication to the network coupled to the GPS engine board, and a position computation circuit to the receiver in the corresponding object, the GPS engine board, receiver and position computation circuit being coupled in each object to the processor in the corresponding object, the processor in each object controlling the GPS engine board in the corresponding object to determine location of the corresponding object, but if the GPS engine board in the corresponding object fails to provide a valid location fix, the processor in the corresponding object then controlling the position computation circuit in the corresponding object to provide a location by dead reckoning based on the last recorded valid location fix.

1 33. The method of claim 32 where providing a location by dead
2 reckoning in the corresponding object comprises using a gyro and a speed
3 sensor in the corresponding object to provide dead reckoning input data and
4 calculating a dead reckoning location using the processor in the corresponding
5 object.

1 34. The method of claim 33 where using a gyro to provide dead
2 reckoning input data in the corresponding object comprises providing three
3 dimensional directional data for the corresponding object.

1 35. The method of claim 18 further comprising communicating in each
2 object through a plurality of input/output ports between the processor and a
3 plurality of external devices coupled the plurality of input/output ports in the
4 corresponding object.

1 36. An apparatus for use with an object characterized by a location in
2 combination with at least one satellite of a global positioning system and a
3 terrestrial location detection network, comprising:
4 a location circuit which detects location information of the object in real-
5 time including a GPS receiver communicating with the at least one satellite of the
6 global positioning system and the terrestrial location detection network;

1002390-12101
TOTAL 062200F

a processor with memory coupled to the location circuit, which processor receives the location information and activates responsive functions according to the object's current location; and
a communications circuit coupled to the location circuit.

37. The apparatus of claim 36 where the processor controls the location circuit to first determine location using the GPS receiver and then uses the terrestrial location detection network to determine location only if the GPS receiver fails to provide valid locational information.

38. The apparatus of claim 36 where the communication circuit comprises a plurality of wireless modems, a satellite modem and a frequency adjustable transceiver coupled to the wireless modems and satellite modem, wherein the processor is coupled to and controls the frequency adjustable transceiver to select a best signal from the wireless modems, but if the best signal from the wireless modems fails to satisfy a predetermined threshold, then the processor controls the frequency adjustable transceiver to select a signal from the satellite modem.

39. The apparatus of claim 36 where the processor stores all valid location fixes and where the location circuit comprises a GPS engine board, a receiver for communication to the network coupled to the GPS engine board, and a position computation circuit coupled to the receiver, the GPS engine board,

5 receiver and position computation circuit being coupled to the processor, where
 6 the processor controls the GPS engine board to determine location of the
 7 corresponding object, but if the GPS engine board fails to provide a valid location
 8 fix, the processor then controls the position computation circuit to provide a
 9 location by dead reckoning based on the last recorded valid location fix.

1 40. The apparatus of claim 39 where the position computation circuit
 2 comprises a gyro and a speed sensor to provide dead reckoning input data from
 3 which the processor calculates a dead reckoning location.

1 41. The apparatus of claim 40 where the gyro comprises a three
 2 dimensional gyro.

1 42. A method used in combination with at least one satellite of a global
 2 positioning system and at least one terrestrially based positioning system
 3 comprising:

4 detecting location information of at least one object in real-time by
 5 selectively communicating a GPS receiver with at least one satellite of the global
 6 positioning system or by selectively communicating a terrestrial receiver with at
 7 least one terrestrially based positioning system; and

8 inputting the location information into a processor with memory in the
 9 object.

1 43. The method of claim 42 where communicating a GPS receiver with
2 at least one satellite of the global positioning system and a terrestrial location
3 detection network in combination comprises controlling a location circuit to first
4 determine location using the GPS receiver and then communicating with the
5 terrestrial location detection network to determine location only if the GPS
6 receiver fails to provide valid locational information.

1 44. The method of claim 42 further comprising transmitting through a
2 plurality of wireless modems, a satellite modem and a frequency adjustable
3 transceiver coupled to the wireless modems and satellite modem, wherein the
4 processor is coupled to and controls the frequency adjustable transceiver to
5 select a best signal from the wireless modems, but if the best signal from the
6 wireless modems fails to satisfy a predetermined threshold, then the processor
7 controls the frequency adjustable transceiver to select a signal from the satellite
8 modem.

1 45. The method of claim 42 further comprising storing all valid location
2 fixes and where detecting location information comprises operating a GPS
3 engine board, a receiver for communication to the network coupled to the GPS
4 engine board, and a position computation circuit coupled to the receiver, the GPS
5 engine board, receiver and position computation circuit being coupled to the
6 processor, the processor controlling the GPS engine board to determine location
7 of the corresponding object, but if the GPS engine board fails to provide a valid

10027390-122101

8 location fix, the processor then controlling the position computation circuit to
 9 provide a location by dead reckoning based on the last recorded valid location
 10 fix.

1 46. The method of claim 45 where providing a location by dead
 2 reckoning comprises using a gyro and a speed sensor to provide dead reckoning
 3 input data and calculating a dead reckoning location using the processor.

1 47. The method of claim 46 where using a gyro to provide dead
 2 reckoning input data comprises providing three dimensional directional data.

1 48. An apparatus for communication to a location-detection network,
 2 including a global positioning satellite system, and for use with an object which is
 3 characterized by a location, comprising:

4 a location circuit installed in the object which detects location information
 5 of the object in real-time independently of the extent of GPS coverage;

6 a processor with memory installed in the object coupled to the location
 7 circuit, which processor receives the location information; and

8 a communication circuit installed in the object and coupled to the
 9 processor to communicate with the location-detection network.

10027390-122101

1 49. The apparatus of claim 48 where the location circuit comprises a
2 GPS receiver communicating with the at least one satellite of the global
3 positioning satellite system.

1 50. The apparatus of claim 48 where the location-detection network
2 includes a terrestrially based location detection network and where the location
3 circuit communicates through the communication circuit with the terrestrially
4 based location detection network.

1 51. The apparatus of claim 1 in further combination with at least one
2 satellite of a global positioning system and where the location circuit comprises a
3 GPS receiver communicating with the at least one satellite of the global
4 positioning system and a terrestrial location detection network in combination.

1 52. The apparatus of claim 51 where the processor controls the
2 location circuit to first determine location using the GPS receiver and then uses
3 the terrestrial location detection network to determine location only if the GPS
4 receiver fails to provide valid locational information.

1 53. The apparatus of claim 48 where the communication circuit
2 comprises a plurality of wireless modems, a satellite modem and a frequency
3 adjustable transceiver coupled to the wireless modems and satellite modem,

1002390-12104
TOTAL 062200

4 wherein the processor is coupled to and controls the frequency adjustable
5 transceiver to select a best signal from the wireless modems, but if the best
6 signal from the wireless modems fails to satisfy a predetermined threshold, then
7 the processor controls the frequency adjustable transceiver to select a signal
8 from the satellite modem.

1 54. The apparatus of claim 48 where the processor stores all valid
2 location fixes and where the location circuit comprises a GPS engine board, a
3 receiver for communication to the network coupled to the GPS engine board, and
4 a position computation circuit coupled to the receiver, the GPS engine board,
5 receiver and position computation circuit being coupled to the processor, where
6 the processor controls the GPS engine board to determine location of the
7 corresponding object, but if the GPS engine board fails to provide a valid location
8 fix, the processor then controls the position computation circuit to provide a
9 location by dead reckoning based on the last recorded valid location fix.

1 55. The apparatus of claim 54 where the position computation circuit
2 comprises a gyro and a speed sensor to provide dead reckoning input data from
3 which the processor calculates a dead reckoning location.

1 56. The apparatus of claim 55 where the gyro comprises a three
2 dimensional gyro.

1 57. A method for communication to a location-detection network,
2 including a global positioning satellite system, and for use with an object, which is
3 characterized by a location, comprising:
4 selectively communicating with selected portions of the location-detection
5 network including a global positioning satellite system;
6 detecting location information of an object in real-time independently of the
7 extent of GPS coverage; and
8 inputting the location information into a processor with memory.

1 58. The method of claim 57 where selectively communicating with
2 selected portions of the location-detection network including a global positioning
3 satellite system comprises communicating a GPS receiver with at least one
4 satellite of the global positioning system and a terrestrial location detection
5 network in combination.

1 59. The method of claim 58 where communicating a GPS receiver with
2 at least one satellite of the global positioning system and a terrestrial location
3 detection network in combination comprises controlling the location circuit to first
4 determine location using the GPS receiver and then communicating with the
5 terrestrial location detection network to determine location only if the GPS
6 receiver fails to provide valid locational information.

1007390-123101

1 60. The method of claim 57 where selectively communicating with
2 selected portions of the location-detection network including a global positioning
3 satellite system comprises transmitting through a plurality of wireless modems, a
4 satellite modem and a frequency adjustable transceiver coupled to the wireless
5 modems and satellite modem, wherein the processor is coupled to and controls
6 the frequency adjustable transceiver to select a best signal from the wireless
7 modems, but if the best signal from the wireless modems fails to satisfy a
8 predetermined threshold, then the processor controls the frequency adjustable
9 transceiver to select a signal from the satellite modem.

1 61. The method of claim 57 further comprising storing all valid location
2 fixes and where detecting location information comprises operating a GPS
3 engine board, a receiver for communication to the network coupled to the GPS
4 engine board, and a position computation circuit coupled to the receiver, the GPS
5 engine board, receiver and position computation circuit being coupled to the
6 processor, the processor controlling the GPS engine board to determine location
7 of the corresponding object, but if the GPS engine board fails to provide a valid
8 location fix, the processor then controlling the position computation circuit to
9 provide a location by dead reckoning based on the last recorded valid location
10 fix.

1 62. The method of claim 61 where providing a location by dead
2 reckoning comprises using a gyro and a speed sensor to provide dead reckoning
3 input data and calculating a dead reckoning location using the processor.

1 63. The method of claim 62 where using a gyro to provide dead
2 reckoning input data comprises providing three dimensional directional data.

10027390-100101